





# OUR BOBBIN ASSORTMENT




### K160

PP or PE approx. 2,0 lbs  
PA approx. 2,5 lbs  
PET or PBT approx. 2,9 lbs





### K355

PP or PE approx. 13,2 lbs  
PA approx. 15,4 lbs  
PET or PBT approx. 17,6 lbs




### K200

PP or PE approx. 4,0 lbs  
PA approx. 4,9 lbs  
PET or PBT approx. 5,5 lbs





### K450/127

PP or PE approx. 55,0 lbs  
PA approx. 66,0 lbs  
PET or PBT approx. 77,0 lbs




### K200E

PP or PE approx. 6,2 lbs  
PA approx. 6,6 lbs  
PET or PBT approx. 7,3 lbs





### D335/180

PP or PE approx. 15,4 lbs  
PA approx. 17,6 lbs  
PET or PBT approx. 22,0 lbs





### K250

PP or PE approx. 6,2 lbs  
PA approx. 6,6 lbs  
PET or PBT approx. 7,3 lbs





### K500

PP or PE approx. 48,5 lbs  
PA approx. 57,0 lbs  
PET or PBT approx. 66,0 lbs




### K250E

PP or PE approx. 7,3 lbs  
PA approx. 10,0 lbs  
PET or PBT approx. 12,0 lbs





### K580

PP or PE approx. 88,0 lbs  
PA approx. 106,0 lbs  
PET or PBT approx. 121,0 lbs



### K250/400 V2



PP or PE approx. 15,5 lbs  
PA approx. 17,7 lbs  
PET or PBT approx. 22,0 lbs



### S350/125


PP or PE approx. 20,0 lbs  
PA approx. 22,0 lbs  
PET or PBT approx. 28,5 lbs

**Conical bobbin construction: ideal as a high-volume weft bobbin**




### K250EL

PP or PE approx. 10,6 lbs  
PA approx. 14,5 lbs  
PET or PBT approx. 18,5 lbs



### H90/360

PE or PP approx. 3,0 lbs  
PA approx. 3,5 lbs  
PET or PBT approx. 4,0 lbs



### H45/300

PE or PP approx. 1,1 lbs  
PA approx. 1,3 lbs  
PET or PBT approx. 1,4 lbs

**The perfect bobbin suitable for both warp and weft monofilament applications!**

All measurements are in inches. The net thread weight per bobbin is approximate and varies based on thread diameter and quality. Alternative bobbins and windings can be provided upon request.